

An attractive bullet and attack resistant counter module with a high security rating.





OVERVIEW

The glass is available in several bullet resistance ratings – G1, G2, R1/S1 & R2. Voice transfer is achieved by the voice grill built into the counter and a separate electrical voice loop can be supplied upon request.

Special item and document pass through options are available for use in conjunction with the standard counter.

LED lighting are optional extras which can be installed in the pelmet section of the counter while venetian blinds can also be supplied as an optional extra for privacy.

APPLICATIONS

ARA Manufacture's Sealeck Securaguard 501 counter module can be used for government and military buildings and company buildings that operate in high threat level areas and require bullet and attack resistance.

SPECIFICATIONS

Counter width: All counter modules are made to order. Standard counter widths are 1200mm, 1500mm, 1800mm, 2100mm & 2400mm. However, special widths can be designed.

Counter height: Standard counter heights are 720mm for disabled access or 910mm for standing access.

Overall height including glazing is 2020mm for disabled access or 2210mm for standing access.

Maximum glass panel height above counter: 1200mm

Finish options: Modules are supplied in standard 304 stainless steel. 316 #4 stainless-steel finish is available. Jambs and heads can be powder-coated to any standard powder-coat finish. Modules can also be supplied bare to suit commercial joinery or as a prefinished unit.

Glazing options: For counters up to and including G2 either 32mm polycarbonate glass clad polycarbonate or all glass BR glazing can be supplied. All counters supplied above the G2 classification will be supplied with glass clad polycarbonate or all glass BR glazing.

For information on the units please refer to our technical data sheets HST20 Type "B" Tray and HST40 501 drawer.



Securaguard 501 counter module





